



VERSALIFT


1 Under the Spa




1A Bracket Assembly Mounted Under The Spa



1B Complete Assembly Under The Spa



2 Bottom Skirt Mount



2A Bracket Assembly



Deciding Where to Install Your Mounting Brackets

When choosing what end of your spa to attach your Versalift, please consider items such as location of the seam in your spa cover, spa controls, steps, etc. Please close your spa cover and ensure that it is sitting squarely on your spa before you start the installation.

To begin your installation, you must first decide where you will mount the universal mounting brackets. **IMPORTANT:** Do not fill the spa prior to installing the bracket under the spa. As shown in the illustrations to the left, you have 2 options- 1- slide the bracket under your spa or 2- at the bottom of the spa.

Your primary concern in making this decision is to find the place that will offer the most support for the mounting of the brackets. Many spa skirts are either made of extremely thin lumber or alternative materials such as resin and may not hold the weight of a waterlogged spa cover. Because of this, we recommend that where possible, you attach the mounting brackets under the spa.

If you cannot slide the brackets under the spa, most spas have an internal frame that would provide more solid wood to drill the brackets into. The dealer where you bought the spa or manufacturer of your spa should be able to provide information on the internal framework.

Care and Maintenance

Congratulations! You have completed your Versalift installation. Please take note of the following points to ensure you have many years of enjoying your Versalift:

- Do not use in very high winds.
- The Versalift is intended for regular weather conditions. A normal cover weighs between 60-80 lbs (25 to 35 kg). Ice and snow can significantly increase this weight.
- Sp International's warranty does not cover any damage due to cover weight exceeding 150 lbs (65 kg).

Warranty

- One year warranty on manufacturing defects.
- Proof of purchase required.

